
International IOR Rectifier

IRFP350

HEXFET® Power MOSFET

- Dynamic dv/dt Rating
- Repetitive Avalanche Rated
- Isolated Central Mounting Hole
- Fast Switching
- Ease of Paralleling
- Simple Drive Requirements



V_{DSS} = 400V


$R_{DS(on)}$ = 0.30Ω

I_D = 16A

Description

Third Generation HEXFETs from International Rectifier provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The TO-247 package is preferred for commercial–industrial applications where higher power levels preclude the use of TO-220 devices. The TO-247 is similar but superior to the earlier TO-218 package because of its isolated mounting hole. It also provides greater creepage distance between pins to meet the requirements of most safety specifications.



TO-247AC

DATA SHEETS

Absolute Maximum Ratings

	Parameter	Max.	Units
I_D @ T_C = 25°C	Continuous Drain Current, V_{GS} @ 10 V	16	A
I_D @ T_C = 100°C	Continuous Drain Current, V_{GS} @ 10 V	10	
I_{DM}	Pulsed Drain Current ①	64	
P_D @ T_C = 25°C	Power Dissipation	190	W
	Linear Derating Factor	1.5	W/°C
V_{GS}	Gate-to-Source Voltage	±20	V
E_{AS}	Single Pulse Avalanche Energy ②	390	mJ
I_{AR}	Avalanche Current ①	16	A
E_{AR}	Repetitive Avalanche Energy ①	19	mJ
dv/dt	Peak Diode Recovery dv/dt ③	4.0	V/ns
T_J T_{STG}	Operating Junction and Storage Temperature Range	-55 to +150	°C
	Soldering Temperature, for 10 seconds	300 (1.6mm from case)	
	Mounting Torque, 6-32 or M3 screw	10 lbf•in (1.1 N•m)	

Thermal Resistance

	Parameter	Min.	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case	—	—	0.65	°C/W
$R_{\theta CS}$	Case-to-Sink, Flat, Greased Surface	—	0.24	—	
$R_{\theta JA}$	Junction-to-Ambient	—	—	40	

OM Sistemas | Fausto Nicasio Sampaio 110 - Jardim California
Londrina - Paraná - Brasil | CEP 86040-460
Tel. / WhatsApp: +55 43 9616-5524 | vendas@omsistemas.com.br

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Test Conditions
$V_{(BR)DSS}$	Drain-to-Source Breakdown Voltage	400	—	—	V	V_{GS}=0V, I_D= 250µA
$\Delta V_{(BR)DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	0.51	—	V/°C	Reference to 25°C, I_D= 1mA
$R_{DS(on)}$	Static Drain-to-Source On-Resistance	—	—	0.30	Ω	V_{GS}=10V, I_D=9.6A ④
$V_{GS(th)}$	Gate Threshold Voltage	2.0	—	4.0	V	V_{DS}=V_{GS}, I_D= 250µA
g_{fs}	Forward Transconductance	10	—	—	S	V_{DS}=50V, I_D=9.6A ④
I_{DSS}	Drain-to-Source Leakage Current	—	—	25	µA	V_{DS}=400V, V_{GS}=0V
		—	—	250		V_{DS}=320V, V_{GS}=0V, T_J=125°C
I_{GSS}	Gate-to-Source Forward Leakage	—	—	100	nA	V_{GS}=20V
	Gate-to-Source Reverse Leakage	—	—	-100		V_{GS}=-20V
Q_g	Total Gate Charge	—	—	150	nC	I_D=16A
Q_{gs}	Gate-to-Source Charge	—	—	23		V_{DS}=320V
Q_{gd}	Gate-to-Drain ("Miller") Charge	—	—	80		V_{GS}=10V See Fig. 6 and 13 ④
$t_{d(on)}$	Turn-On Delay Time	—	16	—	ns	V_{DD}=200V
t_r	Rise Time	—	49	—		I_D=16A
$t_{d(off)}$	Turn-Off Delay Time	—	87	—		R_G=6.2Ω
t_f	Fall Time	—	47	—		R_D=12Ω See Figure 10 ④
L_D	Internal Drain Inductance	—	5.0	—	nH	Between lead, 6 mm (0.25in.) from package and center of die contact
L_S	Internal Source Inductance	—	13	—		
C_{iss}	Input Capacitance	—	2600	—	pF	V_{GS}=0V
C_{oss}	Output Capacitance	—	660	—		V_{DS}= 25V
C_{rss}	Reverse Transfer Capacitance	—	250	—		f=1.0MHz See Figure 5

Source-Drain Ratings and Characteristics

	Parameter	Min.	Typ.	Max.	Units	Test Conditions
I_S	Continuous Source Current (Body Diode)	—	—	16	A	MOSFET symbol showing the integral reverse p-n junction diode.
I_{SM}	Pulsed Source Current (Body Diode) ①	—	—	64		
V_{SD}	Diode Forward Voltage	—	—	1.6	V	T_J=25°C, I_S=16A, V_{GS}=0V ④
t_{rr}	Reverse Recovery Time	—	380	570	ns	T_J=25°C, I_F=16A
Q_{rr}	Reverse Recovery Charge	—	4.7	7.1	µC	di/dt=100A/µs ④
t_{on}	Forward Turn-On Time	Intrinsic turn-on time is neglegible (turn-on is dominated by L_S+L_D)				

Notes:

① Repetitive rating; pulse width limited by max. junction temperature (See Figure 11)

② V_{DD}=50V, starting T_J=25°C, L=2.7mH R_G=25Ω, I_{AS}=16A (See Figure 12)

③ I_{SD}≤16A, di/dt≤200A/µs, V_{DD}≤$V_{(BR)DSS}$, T_J≤150°C

④ Pulse width ≤ 300 µs; duty cycle ≤2%.

OM Sistemas | Fausto Nicasio Sampaio 110 - Jardim California
Londrina - Paraná - Brasil | CEP 86040-460
Tel. / WhatsApp: +55 43 9616-5524 | vendas@omsistemas.com.br




Fig 1. Typical Output Characteristics, T_C=25°C




Fig 2. Typical Output Characteristics, T_C=150°C




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance Vs. Temperature

OM Sistemas | Fausto Nicasio Sampaio 110 - Jardim California
Londrina - Paraná - Brasil | CEP 86040-460
Tel. / WhatsApp: +55 43 9616-5524 | vendas@omsistemas.com.br




Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area

OM Sistemas | Fausto Nicasio Sampaio 110 - Jardim California
Londrina - Paraná - Brasil | CEP 86040-460
Tel. / WhatsApp: +55 43 9616-5524 | vendas@omsistemas.com.br




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case

OM Sistemas | Fausto Nicasio Sampaio 110 - Jardim California
Londrina - Paraná - Brasil | CEP 86040-460
Tel. / WhatsApp: +55 43 9616-5524 | vendas@omsistemas.com.br




Fig 12a. Unclamped Inductive Test Circuit




Fig 12b. Unclamped Inductive Waveforms




Fig 12c. Maximum Avalanche Energy Vs. Drain Current




Fig 13a. Basic Gate Charge Waveform




Fig 13b. Gate Charge Test Circuit

Appendix A: Figure 14, Peak Diode Recovery dv/dt Test Circuit – See page 1505

Appendix B: Package Outline Mechanical Drawing – See page 1511

Appendix C: Part Marking Information – See page 1517

International IOR Rectifier

OM Sistemas | Fausto Nicasio Sampaio 110 - Jardim California
Londrina - Paraná - Brasil | CEP 86040-460
Tel. / WhatsApp: +55 43 9616-5524 | vendas@omsistemas.com.br